



Product Features

- One-touch start-stop & dual quick water inlets, easy operation, no cleaning downtime
- Agile front drive body, magnetic quick swap twin brushes, double cleaning efficiency
- Triple protection: waste basket, float cage, sensor, anti-overflow & anti-clog
- One-touch lift for squeegee & brushes, easy labor-saving control
- Long aluminum squeegee + LED lights, full dry cleaning no blind spots in dim light
- Shock-absorbing PU foam seat, comfy for long-time operation



Technical Parameters

Cleaning width (brush size"inch)	860 mm/17"*2
Squeegee width	1200 mm
Solution tank capacity	200 L
Recovery tank capacity	225 L
Battery	36 V/200 Ah
Drive motor	800W
Vacuum motor	600 W
Brush motor	550 W*2
Continuous operating time	4~5 h
Weight (inc. battery)	555 kg
Max. coverage per hour	7200 m²/h
Product size	1890*1200*1470 mm

Function Description

A detailed diagram of the XS225 scrubber from a rear-three-quarter perspective. Numbered callouts (1-20) point to various components: 1. Tool Basket, 2. Warning Light, 3. Dirty Water Tank Cover, 4. Water Spray Gun, 5. Clean Water Drain Pipe, 6. Suction Hose, 7. Squeegee Assembly, 8. Sewage Drain Pipe, 9. Steering Wheel, 10. Control Panel, 11. Headlight, 12. Seat, 13. Dirty Water Tank, 14. Charging Port, 15. Clean Water Tank, 16. Rear Wheel, 17. Maintenance Access Port, 18. Brush Disc Assembly, 19. Drive Wheel, 20. Bumper.

① Tool Basket	⑥ Suction Hose	⑪ Headlight	⑯ Rear Wheel
② Warning Light	⑦ Squeegee Assembly	⑫ Seat	⑰ Maintenance Access Port
③ Dirty Water Tank Cover	⑧ Sewage Drain Pipe	⑬ Dirty Water Tank	⑱ Brush Disc Assembly
④ Water Spray Gun	⑨ Steering Wheel	⑭ Charging Port	⑲ Drive Wheel
⑤ Clean Water Drain Pipe	⑩ Control Panel	⑮ Clean Water Tank	⑳ Bumper

Detailed Photos

