





ML5.1-SE 51.2V 100Ah 5.12kWh

Module Design Flexible expansion.

Easy Installation Stackable with flexible brackets.


High Safety LFP Cell level monitoring and balancing.

Wide Compatibility Matching with leading inverters.

Eco-Friendly The whole modulenon-toxic, pollution-free.

Product Display:







Model	ML5.1-SE	
Main Parameter		
Battery Type	LiFePO ₄	
Nominal Battery Energy	5.12kWh	
Nominal Capacity	100Ah	
Nominal Voltage	51.2V	
Operating Voltage	44.8 ~ 57.6 V	
Charge/Discharge Current	80A(Recommended)/100A(Max)	
Other Parameter		
Depth of Discharge	90% DOD	
Dimension	480×443×133mm	
Weight	44kg	
Communication	CAN2.0, RS485	
IP Rating	IP20	
Operating Temperature	Charge : $0{\sim}55^{\circ}\text{C}$; Discharge : $-20^{\circ}\text{C} \sim 55^{\circ}\text{C}$	
Shelf Temperature	-20°C~60°C	
Altitude	≤2000 m	
Cycle Life	≥6000 (25°C±2°C, 0.2C / 0.2C, 80%DOD, 70%EOL)	
Warranty	5 Years	
Certification	UN38.3,MSDS, CE	
Compatible Inverters	SMA/Schneider/Victron Energy/Ingeteam/Solis/GoodWe/Growatt/Soplanet/Luxpower/DEYE etc.	

Battery Pack Accessories

Model	Accessories Parts Description	Remark
3U-LBCable150	Battery Parallel Cable (Included)	Battery power and communication parallel connection cable (when using the 3U-bracket floor mount)
3U-LPCable1500	Hybrid inverter Cable (Included)	Battery power and communication cable connect with hybrid inverter
3U-LRfe	Battery Rack Fixed Ears (Included)	Used for battery fixing with 19inch rack or cabinet
3U-Bracket	Battery Brackets (Included)	Simple stacking bracket, 1 unit including 4 pcs brackets, Max. stacking 4 floors



Model: 3U-LBCable150

Details: Pair of 150mm 4AWG Battery power cable (both ends have waterproof terminals) and one 250mm RJ45 communication cable for battery parallel.



Model: 3U-LPCable1500

Details: Pair of 4AWG DC power cable (one end has a waterproof terminal, the other end is M10 copper terminal) and one RJ45 communication cable connect with hybrid inverter. The default length is 1500mm.



Model: 3U-LRfe

Details: Pair of rack fixed ears used for battery fixing with 19inch rack or cabinet.



Model: 3U-Bracket

Details: Simple stacking bracket, height 187mm, 1 set including 4 pcs brackets, Max. stacking 4 floors



Mounting Example



