

Anhui YouKe New Material Technology Co., Ltd.

Technical Data Sheet (TDS)

Product Designation: UCL-058

Product Introduction: UCL-058 resin is an n-butylated high imino melamine crosslinker supplied in n-butanol. Its hydrophobic nature improves substrate wetting, flow and leveling, and humidity and salt spray resistance making it suitable for a wide range of applications including automotive topcoats and general industrial finishes.

Product Characteristics:

- 1. ResponseSubstrate wetting
- 2. High gloss
- 3. Good petrol and acid resistance

APPLICATION AREAS: Automotive OEM clear coats, General industrial coatings

Product Specifications:

Item	Index	Testing Method
Non-Volatiles	74-78%	ISO 3251
Viscosity (23 °C)	1.5- 7Pa.s	ISO 3219
Acid value (as such)	≤ 0.1 mg KOH/g	ISO 2114
Colour APHA (Lico)	Max. 100 APHA	ISO 6271
Appearance	clear and clean	Visual inspection
Mineral Spirit Tolerance (18°C)	4.5-5.1	Dripping method

Packaging Specifications: 200kg/drum (net weight).

Storage Instructions:The shelf life is 1 years under normal storage conditions. Keep away from fire, strong oxidants, and store in a cool and dry place.

Precautions:This product is a chemical product. Please operate in strict accordance with the safety regulations.

Contact Information:

Anhui YouKe New Material Technology Co., Ltd.
Technical Data Sheet (TDS)

Company: Anhui YouKe New Material Technology Co., Ltd.

Address: No. 1055 Taizi Avenue, Cihu High-tech Zone, Ma'anshan City,
Anhui Province, China.

Contact Person: Zhihua Cao

Contact Phone: +86-555-3507111, +86-555-3506830 (fax), +8618805551968