

# GT-10EP Series

## 10~60kVA Modular Online UPS for Power Applications



### Power range

10~60kVA



### Operation

3P/3P, 3P/1P, 1P/1P, Online double conversion



### Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.



### Characteristics

- Modular UPS platform, designed for power industry.  
Prefabricated, hot-swappable modules for easy maintenance and expansion.
- Works with DC control systems for power plants and substations. Ensures uninterrupted power for substations, plants, and critical industrial processes.
- 7-inch LCD touchscreen with color graphics for easy operation and user-friendly interface.
- 220V DC no-neutral design, compatible with DC busbars. Maintains full power without derating.
- Supports rack or tower installation.
- Comprehensive device-level protection for high reliability and strong environmental adaptability.



Model		GT020/10-EP	GT040/10-EP	GT060/10-EP
Rate Power		20kVA/20kW	40kVA/40kW	60kVA/60kW
Main input	Input	3P5W (3P+N+PE)		
	Rate Voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)		
	Rate Freq.	50/60Hz		
	Input PF	>0.99		
	Current distortion	THDi<3% ( 100% Linear load )		
	Voltage range	304 ~ 478VAC(L-L)full load; 304 ~ 228VAC (L-L) power derate from 100% to 50%		
	Freq. range	40-70Hz		
DC Voltage		220VDC (compatible with DC busbars, also supports external battery packs)		
Bypass	Bypass Voltage	380/400/415 VAC (L-L); 220/230/240 VAC(L-N)		
	Voltage range	Settable, Default: -20% ~ +15%; Upper limit options: +10%, +15%, +20%, +25%; Lower limit options: -10%, -15%, -20%, -30%, -40%		
	Overload Capacity	110%,continuous operation;125%,10 mins;150%,1 min		
Output	Rate voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)		
	Rate Freq.	50/60Hz		
	Output PF	1		
	Voltage accuracy	±1.0%		
	Output THDu	<1% (linear load), <5% (non-linear load)		
	Inverter Overload	100 – 110% load: bypass after 1h; 110 – 125% load: bypass after 10min 125 – 150% load: bypass after 1min;150% load: bypass after 200ms		
	Frequency accuracy	0.1%		
	Tracking range	Settable, ±0.5 Hz – ±5 Hz, default ±3 Hz		
	Tracking rate	Settable, 0.5Hz/s – 3Hz/s, default 0.5 Hz/s		
	Three-phase phase accuracy	120° ±0.5°		
	Efficiency	96.5%		
System	Display	LCD + LED + Color Touchscreen 7-inch		
	Certification- Safety	IEC62040-1, IEC60950-1		
	Certification- EMS	IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4 (EFT); IEC61000-4-5 (Surge)		
	IP degree	IP20		
	Configuration	USB, RS232, RS485, Dry contact, Air filter		
	Option	SNMP card, AS400 card, Parallel kit, APP/WiFi/Bluetooth		
	Environment	0-40℃(operation);-25℃~70℃(storage);0-95% (Humidity, non-condensing)		
	Noise (dB) (at 1m)	65dB @ 100% load, 62dB @ 45% load		
Dimensions WxDxH (mm)	Cabinet body	442*710*307(7U)	442*710*485(11U)	442*661*906(20U)
	Cabinet	442*751*397	442*751*575	442*841*976
	Power module	400*495*86(2U)		

Statement: The products will continue to be innovative and optimized, which may lead to asynchronized updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.