

GTM-10/20 Series

10~200kVA Modular UPS



Power Range

10~200kVA

Operation

3P/3P,3P/1P,1P/1P,Online double conversion

Application

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.

Characteristics

- 7 inch touch LCD, with IoT functions.
- Supports 3P/1P,1P/1P flexibility configuration.
- High reliability and environmental adaptability,with protection of components level.
- No disassembly, direct mounted in 19 inch rack, or stand alone.
- Extreme high power density, 20kW in 2U, friendly for space and maintenance.
- Supports supercharging, satisfy high-capacity lithium batteries.
- High charging capacity, fast battery recovery.
- Energy storage mode & parallel supply support for weak grids.



Model		GTM020/10	GTM040/10	GTM060/10
Rate Power		20kVA	40kVA	60kVA
Main input	Input	3P5W (3P+N+PE)		
	Rate Voltage	380/400/415VAC(L-L) 220/230/240VAC(L-N)		
	Rate Freq.	50/60Hz		
	Input PF	>0.99		
	Current distortion	THDi<3%(100% Linear load)		
	Voltage range	304~478VAC(L-L)full load; 304~228VAC (L-L) power derate from 100% to 50%		
	Freq. range	40-70Hz		
Battery	Rate voltage	3 Wires: ± 240 VDC(20-50 PCS selceted); 2 Wires(optional): 480VDC(20-50 PCS selceted)		
	Charging capacity	50%*Pout (Limited by input current)		
	Charging accuracy	$\pm 1\%$		
Bypass	Rate voltage	380/400/415VAC(L-L) 220/230/240VAC(L-N)		
	Voltage range	Range: -40%~ +25% , Settable, default -20%~ +15%;		
	Overload	<110%, long time operation;110%< load<125%, 10 mins 125%<load<150%,1 min		
Inverter	Rate voltage	380/400/415VAC(L-L) 220/230/240VAC(L-N)		
	Rate Freq.	50/60Hz		
	Output PF	1		
	Voltage accuracy	$\pm 1.0\%$		
	Output THDu	<1%(linear load), <5% (non-linear load according to IEC 62040-3)		
	Overload	110%,1 hour; 125%,10 mins; 150%,1 min; >150%,200ms		
	Frequency accuracy	0.1%		
	Synchronize window	Settable, ± 0.5 Hz ± 5 Hz, default ± 3 Hz		
	Slew rate	Settable , 0.5Hz/S-3Hz/S, default 0.5Hz/S		
Phase Accuracy	$120^\circ \pm 0.5^\circ$			
System	Efficiency-normal mode	up to 96.5%		
	Display	LED + 7 inch touch LCD		
	Certification- Safety	IEC62040-1, IEC60950-1		
	Certification- EMS	IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4(EFT); IEC61000-4-5 (Surge)		
	IP degree	IP20		
	Configuration	USB, RS232, RS485, Dry contact, Cold start, Air filter		
	Option	SNMP card, AS400 card, Parallel kit, APP / WiFi / Bluetooth		
	Environment	0-40°C (operation); -25°C~70°C(storage); 0-95% (Humidity, non-condensing)		
	Noise(dB)(1 meter)	65dB @ 100% load, 62dB @ 45% load		
Dimention (W*D*H)mm (default)	Cabinet dimention	442*711*307(7U)	442*710*485 (11U)	442*661*906 (20U)
	MAX dimention	442*751*397	442*751*575	442*841*976
Four-switch cabinet (optional)	Cabinet dimention	442*710*396 (9U)	/	442*661*1239 (28U)
	MAX dimention	442*751*486		442*841*1331
Power Module W*D*H(mm)		400*495*86 (2U)		

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.

Model		GTM040/20	GTM080/20	GTM120/20	GTM200/20	
Rate Power		40kVA/40kW	80kVA/80kW	120kVA/120kW	200kVA/200kW	
Main input	Input	3P5W (3P+N+PE)				
	Rate Voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)				
	Rate Freq.	50/60Hz				
	Input PF	>0.99				
	Current distortion	THDi<3%(100% Linear load)				
	Voltage range	304~478VAC(L-L)full load; 304~228VAC (L-L) power derate from 100% to 50%				
	Freq. range	40-70Hz				
Battery	Rate voltage	3 Wires: ± 240 VDC(20-50 PCS selceted); 2 Wires(optional): 480VDC(20-50 PCS selceted)				
	Charging capacity	50%*Pout (Limited by input current)				
	Charging accuracy	$\pm 1\%$				
Bypass	Rate voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)				
	Voltage range	Range: -40%~ +25%, Settable, default -20%~ +15%				
	Overload	<110%, long time operation;110%< load<125%, 10 mins 125%<load<150%,1 min				
Inverter	Rate voltage	380/400/415VAC(L-L); 220/230/240VAC(L-N)				
	Rate Freq.	50/60Hz				
	Output PF	1				
	Voltage accuracy	$\pm 1.0\%$				
	Output THDu	<1%(linear load), <5% (non-linear load according to IEC 62040-3)				
	Overload	110%,1 hour; 125%,10 mins; 150%,1 min; >150%,200ms				
	Frequency accuracy	0.1%				
	Synchronize window	Settable, ± 0.5 Hz- ± 5 Hz, default ± 3 Hz				
	Slew rate	Settable, 0.5Hz/S-3Hz/S, default 0.5Hz/S				
Phase Accuracy	$120^\circ \pm 0.5^\circ$					
System	Efficiency-normal mode	up to 96.5%				
	Display	LCD+LED + 7 inch touch LCD			LCD+LED + 10 inch touch LCD	
	Certification- Safety	IEC62040-1, IEC60950-1				
	Certification- EMS	IEC62040-2; IEC61000-4-2(ESD); IEC61000-4-3(RS); IEC61000-4-4(EFT); IEC61000-4-5 (Surge)				
	IP degree	IP20				
	Configuration	USB, RS232, RS485, Dry contact, Cold start, Air filter				
	Option	SNMP card, AS400 card, Parallel kit, APP / WiFi / Bluetooth				
	Environment	0-40°C(operation); -25°C~70°C(storage); 0-95% (Humidity, non-condensing)				
	Noise(dB)(1 meter)	65dB @ 100% load, 62dB @ 45% load				
	Dimention (W*D*H)mm (default)	Cabinet dimention	442*710*307(7U)	442*661*705 (16U)	442*661*906 (20U)	600*850*2000
MAX dimention		442*751*397	442*841*797	442*841*976		
Four-switch cabinet (optional)		Cabinet dimention	442*710*396 (9U)	/	442*661*1239 (28U)	600*850*2000
		MAX dimention	442*751*486		442*841*1331	
Power Module W*D*H(mm)		400*495*86 (2U)				

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.