

GTM-20-LV Series

20~160kVA Modular UPS(208V)



Power range

20~160kVA

Operation

3P/3P, Online double conversion

Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.

Characteristics

- Mounted in 19 inch rack, or stand alone.
- 7 inch touch LCD, with IoT functions.
- High reliability and environmental adaptability, with protection of components level.
- Extreme high power density, 20kW in 2U, friendly for space and maintenance.
- Option of 30A charger module for long backup applications.



Model		GTM60/20-LV	GTM100/20-LV	GTM160/20-LV
Rate Power		60kVA/60kW	100kVA/100kW	160kVA/160kW
Main input	Input	3P5W (3P+N+PE)		
	Rate Voltage	200/208/220VAC(L-L)		
	Rate Freq.	50/60Hz		
	Input PF	>0.99		
	Current distortion	THDi<3%(100% Linear load)		
	Voltage range	166 ~261VAC(L-L)full load ; 125 ~166VAC (L-L) power derate from 100% to 50%		
	Freq. range	40-70Hz		
	Rate voltage	±120VDC		
Battery	Charging capacity	20%*Pout		
	Charging accuracy	±1%		
Bypass	Rate voltage	200/208/220VAC(L-L)		
	Voltage range	Range: -40%- +25% , Settable, default -20% ~+15% ;		
	Overload	<110%, long time operation; 110%< load<125%, 10 mins; 125%<load<150%,1 min		
Inverter	Rate voltage	200/208/220VAC(L-L)		
	Rate Freq.	50/60Hz		
	Output PF	1		
	Voltage accuracy	±1.0%		
	Load response	<5% (20% - 80% -20% step load)		
	Recovery time	< 20ms (0% - 100% -0% step load)		
	Output THDu	<1%(linear load),<5% (non-linear load according to IEC 62040-3)		
	Overload	110%,1 hour ; 125%,10 mins ; 150%,1 min ; >150%,200ms		
	Frequency accuracy	0.1%		
	Synchronize window	Settable , ±0.5Hz-±5Hz , default ±3Hz		
	Slew rate	Settable , 0.5Hz/S-3Hz/S , default 0.5Hz/S		
	Phase Accuracy	120°±0.5°		
System	Efficiency	Normal Mode up to 94% ;Battery Mode up to 94%		
	Display	LED + 7 inch touch LCD		LED + 10 inch touch LCD
	Certification- Safety	IEC62040-1, IEC60950-1		
	Certification- EMS	IEC62040-2 ; IEC61000-4-2(ESD) ; IEC61000-4-3(RS) ; IEC61000-4-4 (EFT) ; IEC61000-4-5 (Surge)		
	IP degree	IP20		
	Configuration	USB, RS232, RS485, Dry contact, Cold start		
	Option	SNMP card, AS400 card, Parallel kit, LBS, Air filter, Bottom entry kit		
	Environment	0-40℃(operation) ; -25℃~70℃(storage) ; 0-95% (Humidity, non-condensing)		
	Noise(dB)(1 meter)	65dB @ 100% load, 62dB @ 45% load		
Dimention	cabinet(W*D*H)mm	482*816*796 (18U,wheels not included)	482*816*1018(23U, wheels not included)	600*1000*2000
	module(W*D*H)mm	440*678*85(2U)		
Weight(kg)	Cabinet	113	132	260
	Module	23		
Power Module rated capacity		20KW		

Statement: The products will continue to be innovative and optimized, which may lead to asynchronous updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.