

GTS-Pro Tower Series

6~20kVA 3/1 Tower UPS



Power range

6~20kVA

Operation

3P/1P, 1P/1P, online double conversion

Applications

Government, Finance, IT, Education, Transportation, Broadcasting, Medical, Energy, etc.

Characteristics

- 4.3-inch color touch screen easy operation.
- Digital charging with battery monitoring.
- Online double conversion, full digital control.
- High-speed DSP control for system performance & protection.
- Wide range of input voltage tolerance.
- Adapt to half-wave load.
- Auto fault waveform recording.
- Output PF=1, high load adaptability.

Model	GSS06B-P	GSS10B-P	GSS06L-P	GSS10L-P	GTS10L-P	GTS15L-P	GTS20L-P
Rate Power	6kVA/6kW	10kVA/10kW	6kVA/6kW	10kVA/10kW	10kVA/10kW	15kVA/15kW	20kVA/20kW
Cold start	Default output 50/60Hz						
Input voltage range	110-288VAC (L-N), 100% load@>176VAC; 90% load@>154VAC; 75% load@>132VAC; 50% load@>110VAC				190-499VAC (L-L), 100% load@>305VAC; 90% load@>266VAC; 75% load@>228VAC; 50% load@>190VAC		
Input power factor	≥0.99						
Frequency range	40-70Hz						
Output frequency	50/60Hz, self adaption						
Output power factor	1						
Rate output	220/230/240VAC						
Load regulation	±1%						
Output THDu	≤1%, Linear load; ≤5%, non-linear load						
Transfer time-INV to BYP	0ms						
Efficiency- normal mode	95.5%				94.5%	95%	
Efficiency- ECO mode	98%						
Noise (1 meter)	<58dB				<62dB		
Overload (normal mode)	110%:60mins; 125%:10mins; 150%:30 seconds						
Battery	Model	16 pcs 12V/7Ah		16 pcs 12V/9Ah		External batteries, 16-24 settable	
	Quantity	16 pcs 12V/7Ah		16 pcs 12V/9Ah		External batteries, 16-24 settable	
	Max charging	1A		8A, settable			
	Rate voltage	Default 192VDC, 192-288VDC settable					
Standard	RS232, RS485						
Option	SNMP card, dry contact board, APP/WiFi/Bluetooth, parallel kit, 12A charger, Maintenance bypass switch						
Dimension Cabinet	190*494*550		190*494*338		190*514*500		
W*D*H(mm) Max.	190*606*550		190*606*338		190*564*500		
Weight(kg)	56	60	14	16	30		

Statement: The products will continue to be innovative and optimized, which may lead to asynchronized updates of the actual product and promotional materials. Therefore, this document is for reference only and does not constitute any offer or commitment.