

GEL 6-GFM(G)-100Ah



Specification


Cells Per Unit	6
Voltage Per Unit	12
Capacity	100Ah@20hr-rate to 1.75V per cell @25°C
Internal Resistance	Approx. 7.5 mΩ
Terminal	M8
Max. Discharge Current	1000A (5 sec)
Design Life	15 years (floating charge)
Maximum Charging Current	20.0A
Initial Current	30.0A MAX
Reference Capacity	C3 68.1AH
	C5 78.5AH
	C10 87.7AH
	C20 100.0AH
Float Charging Voltage	13.6 V~13.8 V @ 25°C
	Temperature Compensation: -3mV/C/Cell
Cycle Use Voltage	14.5 V~14.9 V @ 25°C
	Temperature Compensation: -4mV/C/Cell
Operating Temperature Range	Discharge: -40°C~60°C
	Charge: -20°C~50°C
	Storage: -40°C~60°C
Normal Operating Temperature Range	25°C ± 5°C
Self Discharge	Less than 3% at 25°C per month
Container Material	A.B.S. UL94-HB, UL94-V0 Optional.



Application

- Solar/Wind Power System
- Uninterruptible Power Supplies (UPS)
- Electric Power Systems [EPS]
- Emergency Backup Power Supplies
- Communication Power Supplies
- DC Power Supplies
- Auto Control System

Dimensions



Length	330±1mm (12.9 inches)
Width	171±1mm (6.77 inches)
Height	217±1mm (8.46 inches)
Total Height	225±1mm (8.66 inches)
Terminal	Value
M5	6~7 N*m
M6	8~10 N*m
M8	10~12 N*m
Unit: mm	

F12 Terminal

Constant Current Discharge Characteristics : A[25°C]

F.V/Time	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	185.4	145.0	95.4	55.9	33.4	23.1	19.1	16.1	11.0	9.12	5.50
1.65V	176.4	142.1	93.8	55.6	33.2	23.0	19.0	16.0	10.9	9.03	5.30
1.70V	170.1	139.8	93.0	55.1	32.9	22.8	18.9	15.9	10.8	8.95	5.15
1.75V	158.9	134.7	93.2	54.6	32.7	22.7	18.8	15.7	10.7	8.86	5.00
1.80V	146.6	125.6	92.5	53.3	32.1	22.1	18.3	15.4	10.6	8.77	4.70
1.85V	132.5	114.0	87.4	50.7	30.7	21.1	17.4	14.8	10.1	8.51	4.50

Constant Power Discharge Characteristics : WPC[25°C]

F.V/Time	10min	15min	30min	1h	2h	3h	4h	5h	8h	10h	20h
1.60V	329	264	178	108	65.7	45.8	38.0	32.0	21.9	18.2	9.73
1.65V	319	259	176	107	65.3	45.8	37.9	31.9	21.8	18.1	9.56
1.70V	311	256	177	107	64.9	45.6	37.9	31.8	21.6	17.9	9.38
1.75V	293	247	177	106	64.5	45.4	37.5	31.4	21.5	17.7	9.20
1.80V	273	231	176	104	63.6	44.2	36.7	30.9	21.1	17.5	9.03
1.85V	250	211	167	99.2	61.3	42.3	34.9	29.5	20.2	17.0	8.50

Note: The above characteristics data are average values obtained within three charge/discharge cycle not the minimum values.




Amosolar Co., Ltd


www.amo-solar.com / amosolar.en.alibaba.com info@amo-solar.com




Discharge Characteristics Curve




Charge Characteristic Curve for Cycle Use(IU)




Cycle Life in Relation to Depth of Discharge




Relationship Between Charging Voltage and Temperature




Temperature Effects on Capacity



Storage Characteristics



Effect of Temperature on Long Term Life



Relationship of OCV And State of Charge(20°C)

