

## Coadd™ DF-5276

Defoaming Agent

### DESCRIPTION

**Coadd™ DF-5276** is a solution of modified polyacrylate, non-silicone defoaming agent. Suitable for solvent and solvent free coating systems. It has strong defoaming performance and help to surface levelling. This product is the high solid version of **Coadd™ DF-5206**.

### PHYSICAL PROPEERTIES

Appearance	Light yellow liquid
Density (g/ml)	0.9
Active content (%)	70%
Viscosity (mPas, 25℃)	<15000

Note: These properties are only typical, and do not represent product specifications

### APPLICATION CHARACTERISTIC AND ADVANTAGES

**Coadd™ DF-5276** is universal in coating applications, recommended for solvent borne wood and furniture coatings, industrial coating, and architectural coating. It is recommended to add in grinding stage, in the case of post addition, high shear force would be needed to avoid craters.

Suggested dosage (base on the total formulation): 0.05 – 0.5%. Optimum dosage should be determined via a series of laboratory tests.

### SAFETY NOTICE

Before using the products, please refer to SDS for detailed safety data, handling and storage procedures recommended.

### DISCLAIMER

It is common proposal for product usage and demand above information based on our professional knowledge. Due to environmental uncertainty and out of our control from practical process, please test and make evaluation ahead of use to ensure efficient and safe. For your reference, the above information is only for commonly known and use the product. It is guaranteed to meet quality and product specification.

**\*\*Please refer to SDS for more information**