


SM12D Load Cell

Characteristics : large measurement range, high precision, automatic adjustment, automatic reset, fully sealed welding, and high safety factor.

Application: electronic truck scales, dynamic rail scales, large-tonnage material gate scales, tank scales, etc




Dimensions (In mm. 1mm=0.03937 inches)



CAP. / SIZE	S RE
t/mm	
15、20、30	150
50	210
Ib/inches (conversion of above dimensions)	
33069.34～66138.68	59.06
110231.13	82.68

Circuit Diagram:

- Red: + input
- Blue: -input
- White: +output
- Yellow: -output





SUNMOON

日月科技

Specification:

Type	Technical parameters
Nominal load range	10 ~ 50t
Power supply	10~12 VDC
Zero balance	1.0±% of rated output
Analog output	2.0±0.015mV/V
Input resistance (Rlc)	780±20Ω (ohms)
Output resistance (Ro)	700±5Ω (ohms)
Insulation resistance	≥5000 MΩ (Mege-Ohms)
Class precision	0.05%FS
Effect of temperature	0.05%FS/10°C
Operating temperature	-40 ~ +85°C
Safe Load Limit	200% FS
Safety margin against yielding	300% FS
Safety margin against breakage	500% FS
Material material	High performance alloy steel or (chromium ratio>15% stainless steel)
Protection type	IP68



SUNMOON

日月科技
