



Cell: +86-13696771864

Website: www.liweidafrp.com

E-mail: sales@tfcomposite.com

Address: Room 1716, Ldi Building, Qianshan Road, Zhengwu District, Hefei City, Anhui Province, China

Welcome to visit our factory!

Standard FRP Polyester Rebar Series



XY61 Standard FRP Polyester Rebar Series								
Product Part No.	Diameter (mm)	Bolt ultimate load (KN)	Cross section (mm ²)	Ultimate tensile strength (MPa)	Weight (g/m)	Modulus of elasticity (GPa)	Ultimate shear strength (MPa)	Elongation at break (%)
XY61-4	4	12.6	12.6	1000	25	45	>150	2.5
XY61-5	5	19.6	19.6	1000	40			
XY61-6	6	28.3	28.3	1000	55			
XY61-7	7	38.5	38.5	1000	80			
XY61-8	8	50.3	50.3	1000	105			
XY61-10	10	71	78.5	900	165			
XY61-12	12	97	113	850	240			
XY61-14	14	107	133	800	280			
XY61-16	16	142	177	800	370			
XY61-18	18	185	227	800	460			
XY61-20	20	230	284	800	560			
XY61-22	22	275	346	800	700			
XY61-25	25	340	452	750	950			
XY61-28	28	430	573	750	1220			
XY61-30	30	500	661	750	1350			
XY61-32	32	570	755	750	1550			
XY61-36	36	725	962	750	2040			
XY61-40	40	837	1195	700	2540			

FRP Bolt Series



XY60-ER FRP Anchor Bolt Series (Epoxy Resin)													
Product Part No.	Diameter (mm)	Bolt ultimate load (KN)	Thread ultimate load (KN)		Cross section (mm ²)	Ultimate tensile strength (MPa)	Torque (Nm)	Weight (g/m)	Modulus of elasticity (GPa)	Ultimate shear strength (MPa)	Bending strength (MPa)	Elongation at break (%)	Antistatic value (Ω)
			Steel	FRP									
XY60-16-ER	16	165	/	45	165	1000	50	350	45	>150	>650	2.5	≤3x10 ⁸
XY60-18-ER	18	215	/	50	240	1000	60	460					
XY60-20-ER	20	269	80	60	269	1000	80	560					
XY60-22-ER	22	330	100	60	330	1000	100	690					
XY60-24-ER	24	360	150	70	398	900	120	860					
XY60-25-ER	25	390	180	70	434	900	140	930					
XY60-27-ER	27	435	200	80	511	850	150	1050					
XY60-28-ER	28	470	200	80	552	850	160	1200					
XY60-30-ER	30	540	220	80	638	850	200	1350					
XY60-32-ER	32	620	250	90	731	850	250	1550					
XY60-38-ER	38	890	420	100	1046	850	/	2250					
XY60-40-ER	40	930	420	100	1164	800	/	2480					
XY60-51-ER	51	1540	/	/	1924	800	/	4100					

XY60 Standard FRP Polyester Anchor Bolt Series													
Product Part No.	Diameter (mm)	Bolt ultimate load (KN)	Thread ultimate load (KN)		Cross section (mm ²)	Ultimate tensile strength (MPa)	Torque (Nm)	Weight (g/m)	Modulus of elasticity (GPa)	Ultimate shear strength (MPa)	Bending strength (MPa)	Elongation at break (%)	Antistatic value (Ω)
			Steel	FRP									
XY60-16	16	125	/	45	165	750	35	350	45	>150	>400	2.5	≤3x10 ⁸
XY60-18	18	150	/	50	240	700	45	460					
XY60-20	20	200	80	60	269	700	60	560					
XY60-22	22	250	100	60	330	700	80	690					
XY60-24	24	280	150	70	398	700	100	860					
XY60-25	25	320	180	70	434	700	120	930					
XY60-27	27	380	200	80	511	700	130	1050					
XY60-28	28	400	200	80	552	700	130	1200					
XY60-30	30	470	220	80	638	700	180	1350					
XY60-32	32	550	250	90	731	700	230	1550					
XY60-38	38	750	420	100	1046	700	/	2250					
XY60-40	40	790	420	100	1164	650	/	2480					
XY60-51	51	1255	/	/	1924	650	/	4100					