

Wall-Mounted

Energy Storage Battery



51.2V









SUNERGY USA WORKS LLC Email: info@sunergyworks.com

Add: 1330 St Mary's Street,Ste 330,Wake Raleigh,NC 27505,USA Web: www.sunergyworks.com

BATTERY FEATURES

- Original Grade A lithium iron phosphate battery cell has high safety and reliability
- The charging and discharging efficiency is high, and the number of cycles is more than 3500 times
- Compatible with most inverters on the market
- Supporting RS485 and CAN communication
- Modular design, can be expanded at any time to increase the energy of the system
- Supporting up to 15 batteries in parallel
- ON/OFF switch control output
- The LCD display monitors the operating status in real time

Product Model	SUN5100V ₁	SUN5200V ₂
Cells In Series	16S	16S
Rated Energy (KWh)	5.12	10.24
Rated Voltage (V)	51.2	51.2
Charging Voltage (V)	58.4	58.4
Discharge Cut-off Voltage (V)	42	42
Standard Charge Current (A)	20	40
Maximum Charging Current (A)	100	100
Maximum Discharge Current (A)	100	100
Features		
Cycle Life	≥ 3500 times @ 80% DOD, 25 °C	≥ 3500 times @ 80% DOD, 25 °C
Methods Of Communication	RS232/RS485/CAN	RS232/RS485/CAN

reatures		
Cycle Life	≥ 3500 times @ 80% DOD, 25 °C	≥ 3500 times @ 80% DOD, 25 °C
Methods Of Communication	RS232/RS485/CAN	RS232/RS485/CAN
Charging Temperature	0~60°C	0~60°C
Discharge Temperature	-10~65°C	-10~65°C
How It Is Displayed	LCD display	LCD display
IP Protection	IP 21	IP 21
Conventional		

Conventional		
Product Dimensions (L×W×Hmm)	440×150×560	520×150×680
Net Weight (Kg)	44	80
Packing Dimensions (L×W×Hmm)	525×340×645	595×316×755
Gross Weight (Kg)	50	95

FIELDS OF APPLICATION

Wall-Mounted Energy Storage LiFePO4 Battery, and the main use areas are as follows:

Standby power

Machine shop

Home energy storage

Solar storage •••





